


JZ-600 flexible, number coded, 0,6/1kV, meter marking**Technical data**

- Special PVC control cable adapted to DIN VDE 0262 and DIN VDE 0285-525-2-51 / DIN EN 50525-2-51, with insulation wall thickness for 1 kV
- **Temperature range** flexing -15°C to +80°C fixed installation -40°C to +80°C
- **Nominal voltage** U_0/U 0,6/1 kV
- **Test voltage** 4000 V
- **Breakdown voltage** min. 8000 V
- **Insulation resistance** min. 20 MΩm x km
- **Minimum bending radius** flexing 7,5x cable Ø fixed installation 4x cable Ø
- **Radiation resistance** up to 80×10^6 cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper-conductor, to DIN VDE 0295 cl.5, fine-wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of special PVC compound type T12 to DIN VDE 0207-363-3 / DIN EN 50363-3
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay-length
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1 / DIN EN 50363-4-1
- Sheath colour black (RAL 9005)
- with meter marking

Properties

- Extensively oil resistant, oil-/chemical resistance see table Technical Informations
 - The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers
 - **UV-resistant**
- Tests**
- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)

Note

- G = with green-yellow conductor x = without green-yellow conductor (OZ)
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- screened analogue type: **JZ-600-Y-CY**, confer page 60

Application

Wiring cable for measuring and controlling purposes in tool machinery, conveyor belts and production lines, for plant installations, air conditioning and in steel production plants and rolling mills. Suitable for installation for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outside (fixed installation). Is not suitable to be used as direct burial (suitable from an outer diameter of 18,0 mm for direct burial) or as underwater cable. The cores have been numbered in such a way that the numbers are easily identifiable, even if the cable has only been stripped back a few cm. The core numbers have been underlined to avoid confusion. The earth core is located in the outer layer. The black, special PVC outer sheath is resistant to the ultra violet radiation. Mainly used in South-European, Eastern and Arabian countries.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10550	2 x 0,5	6,3	9,6	56,0	20
10551	3 G 0,5	6,6	14,4	68,0	20
10552	3 x 0,5	6,6	14,4	68,0	20
10553	4 G 0,5	7,2	19,0	100,0	20
10554	4 x 0,5	7,2	19,0	100,0	20
10555	5 G 0,5	8,0	24,0	117,0	20
10556	5 x 0,5	8,0	24,0	117,0	20
10557	6 G 0,5	8,7	29,0	126,0	20
10558	7 G 0,5	8,7	33,6	138,0	20
10559	7 x 0,5	8,7	33,6	138,0	20
10560	8 G 0,5	9,5	38,0	150,0	20
10561	8 x 0,5	9,5	38,0	150,0	20
10562	10 G 0,5	10,3	48,0	176,0	20
10563	12 G 0,5	11,2	58,0	200,0	20
10564	12 x 0,5	11,2	58,0	200,0	20
10565	14 G 0,5	12,3	67,0	230,0	20
10566	16 G 0,5	12,9	76,0	250,0	20
10567	18 G 0,5	13,8	86,0	276,0	20
10568	20 G 0,5	14,4	96,0	293,0	20
10569	21 G 0,5	14,4	96,0	305,0	20
10570	25 G 0,5	16,1	120,0	335,0	20
10571	30 G 0,5	17,2	144,0	348,0	20
10572	32 G 0,5	18,0	154,0	355,0	20
10573	34 G 0,5	18,7	163,0	520,0	20
10574	40 G 0,5	19,5	192,0	590,0	20
10575	42 G 0,5	20,1	202,0	595,0	20
10576	50 G 0,5	22,1	240,0	715,0	20
10577	52 G 0,5	22,1	252,0	740,0	20
10578	61 G 0,5	23,6	293,0	840,0	20
10579	65 G 0,5	24,4	312,0	880,0	20
10580	80 G 0,5	27,2	384,0	960,0	20
10581	100 G 0,5	31,2	480,0	1050,0	20

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10582	2 x 0,75	6,6	14,4	66,0	19
10583	3 G 0,75	6,9	21,6	74,0	19
10584	3 x 0,75	6,9	21,6	74,0	19
10585	4 G 0,75	7,5	29,0	126,0	19
10586	4 x 0,75	7,5	29,0	126,0	19
10587	5 G 0,75	8,4	36,0	140,0	19
10588	5 x 0,75	8,4	36,0	140,0	19
10589	6 G 0,75	9,3	43,0	170,0	19
10590	6 x 0,75	9,3	43,0	170,0	19
10591	7 G 0,75	9,3	50,0	190,0	19
10592	7 x 0,75	9,3	50,0	190,0	19
10593	8 G 0,75	10,3	58,0	212,0	19
10594	8 x 0,75	10,3	58,0	212,0	19
10595	9 G 0,75	11,0	65,0	227,0	19
10596	10 G 0,75	11,0	72,0	238,0	19
10597	12 G 0,75	12,0	86,0	257,0	19
10598	12 x 0,75	12,0	86,0	257,0	19
10599	14 G 0,75	12,9	101,0	286,0	19
10600	15 G 0,75	13,8	108,0	319,0	19
10601	18 G 0,75	14,5	130,0	362,0	19
10602	20 G 0,75	15,4	144,0	394,0	19
10603	21 G 0,75	15,4	151,0	422,0	19
10604	25 G 0,75	17,2	180,0	486,0	19
10605	32 G 0,75	19,0	230,0	595,0	19
10606	34 G 0,75	19,9	245,0	638,0	19
10607	37 G 0,75	19,9	260,0	696,0	19
10608	40 G 0,75	20,7	288,0	726,0	19
10609	41 G 0,75	21,6	296,0	750,0	19
10610	42 G 0,75	21,6	302,0	770,0	19
10611	50 G 0,75	23,7	360,0	895,0	19
10612	61 G 0,75	25,3	439,0	1070,0	19
10613	65 G 0,75	26,3	468,0	1110,0	19
10614	80 G 0,75	28,9	576,0	1500,0	19
10615	100 G 0,75	32,2	720,0	1889,0	19

Continuation ▶